


WeatherShield® Chimney Cap

INSTALLATION INSTRUCTIONS


For Round Chimneys — WSA & WSA-TDW Models

Installs quickly, easily, and securely



1. ASSEMBLE

The WeatherShield is packed in the box ready to assemble. Move hoop upward to vertical position, remove wing nut. Center the screen on bottom plate. Position top plate so the screw at the top of the hoop fits through center hole of the top plate. Secure with wing nut as shown.




2. ROUND FLUES

WeatherShield chimney caps fit inside round metal and masonry flues. Press the pipe end of the WeatherShield into flue until the fit is snug.

3. WATER TIGHT SEAL

Apply a thin film of silicone caulking (not furnished, but available from your local home center) to seal the joint between the Weathershield and the top of the chimney.




4. AIR COOLED CHIMNEYS REQUIRE TDW MODELS

DO NOT bend the three spacers located on the underside of the TDW models. The spacers maintain ventilation space between the bottom of the WeatherShield and the top of the chimney. This is essential for uninterrupted air flow through the cooling channels in air cooled chimneys.

5. SQUARE & RECTANGULAR CHIMNEYS

An Adaptor™ is required for Weathershield installations on square and rectangular chimneys and must be purchased separately. See the Accessories List. The WeatherShield fits inside the round collar on the Adaptor.



6. SCREENS

1/2" Spark Arrestor screens are required in some states such as California. See Accessories list.

**Problem Solving Chimney Products
from the Leader in Chimney Technology**



IMPROVED CONSUMER
PRODUCTS INC.

P.O. Box "B", Attleboro Falls, MA 02763
(508) 695-7000 FAX (508) 695-4209

© Copyright 1997 ICP
IW-97-A